

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **DUALCURE SX DTM FINISH 60**

Article number: 171i2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Application of the substance / the mixture Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Baril Coatings BV
 Zilverenberg 9
 NL-5234 GL 's-Hertogenbosch

Further information obtainable from:

Product Safety Department
 R&D department

1.4 Emergency telephone number:

NVIC: +31(030) 2748888

Only for the purpose of informing medical personnel in cases of acute intoxications.

Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

Sustainable Coating Solutions



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane

Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 1)

· Hazard statements

- H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Resin mixture

· Dangerous components:

| | | |
|--|--|---------|
| CAS: 136210-32-7 ELINCS: 412-060-9 Index number: 607-350-00-9 Reg.nr.: 01-0000015937-58 | bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412 | 20-<25% |
| CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 | xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 10-<15% |
| CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 | 10-<15% |
| CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40 | trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 3-<5% |
| CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | 1-<2.5% |
| ELINCS: 432-430-3 Index number: 616-200-00-1 | mixture of: N,N'-ethane-1,2-diylbis(hexanamide); 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide; N,N'-ethane-1,2-diylbis(12-hydroxyoctadecanamide) Aquatic Chronic 4, H413 | 1-<2.5% |
| CAS: 41556-26-7 EINECS: 255-437-1 Reg.nr.: 01-2119491304-40 | Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317 | 0.5-<1% |

(Contd. on page 3)

EU

Safety data sheet
according to 1907/2006/EC, Article 31




Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 2)

| | | |
|--|---|-----------|
| CAS: 82919-37-7 EINECS: 280-060-4 | methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Sens. 1, H317 | 0.1-0.15% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32 | zinc oxide  Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 0.1-0.15% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 3)

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

| | |
|-------|--|
| IOELV | Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin |
|-------|--|

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|-------|--|
| IOELV | Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin |
|-------|--|

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|--------------------|------------------------------------|
| · Form: | Fluid |
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

| | |
|-------------|-----------------|
| · pH-value: | Not determined. |
|-------------|-----------------|

· Change in condition

| | |
|--|---------------|
| · Melting point/freezing point: | Undetermined. |
| · Initial boiling point and boiling range: | 36 °C |

| | |
|----------------|-------|
| · Flash point: | 30 °C |
|----------------|-------|

| | |
|------------------------------|-----------------|
| · Flammability (solid, gas): | Not applicable. |
|------------------------------|-----------------|

| | |
|-------------------------|--------|
| · Ignition temperature: | 500 °C |
|-------------------------|--------|

| | |
|------------------------------|-----------------|
| · Decomposition temperature: | Not determined. |
|------------------------------|-----------------|

| | |
|------------------------------|------------------------------|
| · Auto-ignition temperature: | Product is not selfigniting. |
|------------------------------|------------------------------|

| | |
|-------------------------|---|
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|-------------------------|---|

· Explosion limits:

| | |
|----------|------------|
| · Lower: | 1.1 Vol % |
| · Upper: | 10.8 Vol % |

| | |
|--------------------|-----------------|
| · Vapour pressure: | Not determined. |
|--------------------|-----------------|

| | |
|---------------------|-------------------------|
| · Density at 20 °C: | 1.602 g/cm ³ |
|---------------------|-------------------------|

| | |
|--------------------|-----------------|
| · Relative density | Not determined. |
|--------------------|-----------------|

| | |
|------------------|-----------------|
| · Vapour density | Not determined. |
|------------------|-----------------|

| | |
|--------------------|-----------------|
| · Evaporation rate | Not determined. |
|--------------------|-----------------|

· Solubility in / Miscibility with water:

| |
|-----------------------------------|
| Not miscible or difficult to mix. |
|-----------------------------------|

| | |
|---|-----------------|
| · Partition coefficient: n-octanol/water: | Not determined. |
|---|-----------------|

· Viscosity:

| | |
|-----------------------|-----------------|
| · Dynamic: | Not determined. |
| · Kinematic at 20 °C: | 79 s (ISO 6 mm) |

· Solvent content:

| | |
|---------------------|---------|
| · Organic solvents: | 17.3 % |
| · VOC (EC) | 21.67 % |

| | |
|-------------------|--------|
| · Solids content: | 82.7 % |
|-------------------|--------|

| | |
|-------------------------|--|
| · 9.2 Other information | No further relevant information available. |
|-------------------------|--|

EU

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 5)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

| | | |
|--------|------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

7779-90-0 trizinc bis(orthophosphate)

| | | |
|------|------|--------------------|
| Oral | LD50 | >5,000 mg/kg (rat) |
|------|------|--------------------|

64742-95-6 Solvent naphtha (petroleum), light arom.

| | | |
|------------|----------|--------------------|
| Oral | LD50 | >6,800 mg/kg (rat) |
| Dermal | LD50 | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60




(Contd. of page 6)

- Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR/RID/ADN, ADN, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR/RID/ADN, ADN** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (trizinc bis(orthophosphate), Solvent naphtha (petroleum), light arom.), MARINE POLLUTANT
- **IMDG** PAINT
- **IATA** PAINT
- **14.3 Transport hazard class(es)**
- **ADR/RID/ADN, IMDG**
- 

- **Class** 3 Flammable liquids.
- **Label** 3
- **ADN**
- **ADN/R Class:** 3 Flammable liquids.
- **IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR/RID/ADN, IMDG, IATA** III
- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: trizinc bis(orthophosphate)
- **Marine pollutant:** Symbol (fish and tree)
- **Special marking (ADR/RID/ADN):** Symbol (fish and tree)
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 30
- **EMS Number:** F-E,S-E

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 7)

| | |
|--|--|
| · Stowage Category | A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR/RID/ADN | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane
Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.04.2019

Version number 389

Revision: 13.03.2019

Trade name: DUALCURE SX DTM FINISH 60

(Contd. of page 8)

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
- **Department issuing SDS:** product safety department
- **Contact:** Mr. Frank van Hofwegen
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
- *** Data compared to the previous version altered.**

EU