

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** STEELKOTE PU FINISH 30 UV+
- **Article number:** 811
- **UFI:** 8942-H04M-X00J-C82V
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**  
 PROC10 Roller application or brushing  
 PROC7 Industrial spraying
- **Technical function** Dye
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Baril Coatings BV  
 Zilverenberg 9  
 NL-5234 GL 's-Hertogenbosch
- **Further information obtainable from:**  
 Product Safety Department  
 R&D department
- **1.4 Emergency telephone number:**  
 NVIC: +31(030) 2748888  
 Only for the purpose of informing medical personnel in cases of acute intoxications.  
 Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

Sustainable Coating Solutions



## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3          H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2          H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard statements**  
 H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

Trade name: **STEELKOTE PU FINISH 30 UV+**

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains Vetzuren, tall-olie, verbindingen met oleylamine. May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

· **Description:** Resin mixture

**Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	20-<25%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO <sub>2</sub> ) substance with a Community workplace exposure limit	5-<7%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	3-<5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	3-<5%
CAS: 128601-23-0 EC number: 918-668-5	Hydrocarbons C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	3-<5%
CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28	Vetzuren, tall-olie, verbindingen met oleylamine ⚠ STOT RE 2, H373; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	0.25-0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

**Trade name: STEELKOTE PU FINISH 30 UV+**

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**  
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
 No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
 Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**

**CAS: 1330-20-7 xylene**

IOELV	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

(Contd. on page 4)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

Trade name: **STEELKOTE PU FINISH 30 UV+**

(Contd. of page 3)

<b>CAS: 14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
BOELV	Long-term value: 0.1 * mg/m <sup>3</sup> *respirable fraction
<b>CAS: 108-65-6 2-methoxy-1-methylethyl acetate</b>	
IOELV	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
<b>CAS: 100-41-4 ethylbenzene</b>	
IOELV	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:**

Fluid

**Colour:**

According to product specification

· **Odour:**

Characteristic

(Contd. on page 5)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

Trade name: STEELKOTE PU FINISH 30 UV+

(Contd. of page 4)

· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b> <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	137-143 °C
· <b>Flash point:</b>	30 °C
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7 Vol %
· <b>Vapour pressure at 20 °C:</b>	6.7-8.2 hPa
· <b>Density at 20 °C:</b>	1.395 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	70 s (ISO 6 mm)
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	35.6 %
<b>VOC (EC)</b>	35.59 %
<b>Solids content:</b>	69.9 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

Trade name: **STEELKOTE PU FINISH 30 UV+**

(Contd. of page 5)

· <b>LD/LC50 values relevant for classification:</b>		
<b>CAS: 1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

CAS: 1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· **Primary irritant effect:**· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.· **Additional toxicological information:**· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.· **Carcinogenicity** Based on available data, the classification criteria are not met.· **Reproductive toxicity** Based on available data, the classification criteria are not met.· **STOT-single exposure** Based on available data, the classification criteria are not met.· **STOT-repeated exposure** Based on available data, the classification criteria are not met.· **Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:** No further relevant information available.· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR/RID/ADN, ADN, IMDG**

Void

· **IATA**

UN1263

(Contd. on page 7)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**


Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

Trade name: STEELKOTE PU FINISH 30 UV+

(Contd. of page 6)

· <b>14.2 UN proper shipping name</b> · <b>ADR/RID/ADN, ADN, IMDG</b> · <b>IATA</b>	Void PAINT
· <b>14.3 Transport hazard class(es)</b> · <b>ADR/RID/ADN, IMDG</b> · <b>Class</b>	Void
· <b>ADN</b> · <b>ADN/R Class:</b>	Void -
· <b>IATA</b>  	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids. 3
· <b>14.4 Packing group</b> · <b>ADR/RID/ADN, IMDG</b> · <b>IATA</b>	Void III
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR/RID/ADN</b> · <b>Remarks:</b>	> 450 l: 3 F1, III
· <b>IMDG</b> · <b>Remarks:</b>	> 450 l: 3, III
· <b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 8)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

**Trade name: STEELKOTE PU FINISH 30 UV+**

(Contd. of page 7)

**· Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Directive 2012/18/EU**

- Named dangerous substances - ANNEX I** None of the ingredients is listed.
- Seveso category** P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**· REGULATION (EU) 2019/1148**

**· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**· Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS:** product safety department

- Contact:** Mr. Frank van Hofwegen

**· Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.04.2021

Version number 1

Revision: 26.04.2021

**Trade name: STEELKOTE PU FINISH 30 UV+**

(Contd. of page 8)

*VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

EU